





FLOOR Logos White

Logos, cemento gentile, equilibrio perfetto.

Logos, gentle concrete, perfect balance.



GRES PORCELLANATO - PORCELAIN TILES

CARATTERISTICHE TECNICHE
TECHNICAL FEATURES

EN 14411 (ISO 13006) Appendice G, Gruppo Bla, Ev ≤ 0,5% / Annex G, Group Bla, Ev ≤ 0,5%



	B.C.R.A	D.C.O.F. Test	BS EN 16165 anx C (ex BS 7976)	DIN EN 16165 anx B (ex DIN 51130)	DIN EN 16165 anx A (ex DIN 51097)	ISO 10545-13
Naturale / Matt	> 0,40	≥ 0,50 WET	≥ 36 DRY ≥ 36 WET	R10	A + B	A-LA-HA
Grip / Grip	> 0,40	≥ 0,55 WET	≥ 36 DRY ≥ 36 WET	R11	A+B+C	A-LA-HA
Strutturato / Textured HiThick	> 0,40	≥ 0,55 WET	≥ 36 DRY ≥ 36 WET	R11	A+B+C	A-LA-HA



CODICE PRODOTTO PRODUCT CODE	Spessore Thickness	White	Beige	Greige	Grey	
NATURALE / MATT						
 60x120 cm rett. / 24"x48" rect.	8 mm	J985	J986	J987	J988	
 60x60 cm rett. / 24"x24" rect.	8 mm	J989	J990	J991	J992	
 30x60 cm rett. / 12"x24" rect.	8 mm	J993	J994	J995	J996	
GRIP / GRIP						
 60x60 cm rett. / 24"x24" rect.	8 mm	-	J997	J998	J999	
STRUTTURATO / TEXTURED HITHICK*						
 60x60 cm rett. / 24"x24" rect.	20 mm	-	K010	K011	K012	
PEZZI SPECIALI SPECIAL PIECES						
 Battiscopa rett. 7,2x60 cm / 3"x24"	White	Beige	Greige	Grey		
	K013	K014	K015	K016		
IMBALLI PACKAGING						
	Pcs/Box	Mq/Box	Kg/Box	Box/Pallet	Mq/Pallet	Kg/Pallet
60x120 cm rett. / 24"x48" rect.	2	1,44	30,35	35	50,4	1062,25
60x60 cm rett. / 24"x24" rect.	4	1,44	28,00	32	46,08	896
30x60 cm rett. / 12"x24" rect.	7	144	26,2	40	57,6	1048
60x60 cm HiThick rett. / 24"x24" HiThick rect.	2	0,72	32,24	30	21,6	967,2
Battiscopa 7,2x60 cm rett. / 3"x24" rect.	12	7,2 ml	10	80	576 ml	800
Note. Notes.						
I Notes. Hinweis. Notas. Примечания.						



FLOOR Logos Beige